Certificate of Location of Government Corner

ID#:522506 **Description:** 1/4 SEC COR 25 26 52 **Date Set:** 10/2/1978 **County:** Olmsted

Section: 25 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.5'
County Survey Disk in NW side blazed 21" Maple NE 44.53'
County Survey Disk in SW side blazed (Minnesota Highway Disk beneath blaze) 19" Maple ESE 12.57'
Minnesota Highway Disk in root on E side 17" blazed Maple SSE 67.73'
Post 1' east
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 25 and 26. 40.00 chs. Set quarter section post. Red Oak 12 in. N35ºE 35 lks. Red Oak 7 in. S78ºW 92 lks.

5-1877 Thomas Hunter (Book A P. 312 No. 306), County Surveyor, states: "at H (1/4 Cor. 25-26) Found an old stake standing, not marked, but all traces of witness trees were gone, not even the remains of a stump to be found to correspond with the field notes. The stake found Mr. Schemerhorn says was set by a Surveyor, who ran through from corner to corner of the Section and set the stake midway between which would be correct, when the original stake & witness tree and all other evidence of where the original corner stood are gone, so we assumed the stake found to be correct letting it remain as found." He set stakes at the 1/16th West, the Center 26, and the 1/16th West of the Center 26.

4-1878 Hunter (Book A P. 336 No. 330) states: "at I (1/4 Cor. 25-26) - Found stake as described at "H" in Survey No. 306 and our measurement from E to K the section corners agrees with the stake found at I (or "H" in survey No. 306) and corroberates (?) the statement there made-Set new stake in its place." He then set the 1/16th East, the Center 25, the 1/16th East of the Center 25, and the 1/16th South. He shows measures North and South of 39.92 chs.

4-1893 William Fraser (Book A P. 505 No. 475) found the stake P. 336 and also the stake at the 1/16th South.

6-1973 County Surveyor set a 1/2" rod between two limestones.

10-2-1978 County Surveyor after finding stones at the 1/16th West of the Center 26 and the 1/16th East of the Center 26 and extending the line East across these stones, we dug in line with the fence South and found a 2" diameter stake 12+" long reaching into clay. We also found a 2"x10"x12" limestone standing 2.0' South and 1.0' East. We set a C.I.M. as the corner over a 3/4"x12" rod driven in the stake hole and set the stone along side. This location also brought the fence at the 1/16th South midway and came on line from the E. 1/4 Cor. 25 over the E-W fence near the Center 25. The corner is 14.88' North and .23' West of the 1/2" rod set in 1973 (removed).

2-11-2011 County survey crew found CIM down 0.5' in good condition.