Certificate of Location of Government Corner

ID#: 522509 **Description:** SEC CEN 25 52 **Date Set:** **County:** Olmsted

Section: 25 **Township:** 105N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

4-16-1878 Thomas Hunter, County Surveyor, (Book A, Page 336, Survey No. 330) set stake at intersecting quarter lines. 1/16th South set stake midway and on line at 20.10-1/2 chains (1326.93') to South 1/4. 1/16th East set stake midway and on line at 19.91-1/2 chains (1314.39') to East 1/4. 1/16th West set stake midway and on line at 20.07 chains (1324.62') to West 1/4. 1/16th Center of NE 1/4 set stake midway and on line at 20.03-3/4 chains (1322.48') on north-south sixteenth line. 1/16th Center of SW 1/4 set stake midway and on line at 20.05-1/2 chains (1323.63') on east-west sixteenth line.

4-24-1893 William Fraser, Deputy County Surveyor, (Book A, Page 505, Survey No. 475) 1/16th South found stake and set new stake. 1/16th Center of SW 1/4 could not find stake. Set stake midway and on line at 19.93-1/2 chains (1315.71') on east-west sixteenth line.

9-17-1979 MnDOT used computed center at intersecting quarter lines for Minnesota Department of Transportation Right of Way Plats No. 55-13 & 55-14.

8-5-1981 Yaggy Associates used computed center at intersecting quarter lines.

12-3-2004 GGG used computed center at intersecting quarter lines.

5-22-2018 G-Cubed used computed center at intersecting quarter lines.