Certificate of Location of Government Corner

ID#:522605 **Description:** SEC COR 26 27 34 35 52 **Date Set:** 8/9/1978 **County:** Olmsted

Section: 26 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is at the surface
The corner falls under N-S fence
County Survey Disk in E side 26" blazed Hard Maple NNW 101.32'
County Survey Disk in NE side 2 1/2" Maple SE 11.13'
Post w/sign 1' east
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 34 and 35. 80.00 chs. Set post corner to sections 26-27-34-35. Elm 8 in. S62ºE 10 lks. Elm 10 in. S88ºW 8 lks. Elm 15 in. N33ºW 53 lks. Elm 9 in. N57ºE 13 lks.

2-1902 William Fraser, County Surveyor, (Book B P. 30) found the old stake remains with the SE and SW bearing trees standing and the NE and NW bearing tree stumps plain. Set a 1 1/2" iron bar 4' long as the corner. Set a sleigh shoe at the 1/16th South.

8-4-1978 County Surveyor found Fraser's 1 1/2" iron shaft (up 4") in the N-S fence line. Also found Fraser's iron at the 1/16th South.

8-9-1978 County Surveyor drove Fraser's iron down and set a CIM over it. Set a survey marker sign .9' East.

4-18-2011 County survey crew found CIM in good condition