Certificate of Location of Government Corner

ID#:522704 **Description:** 1/4 SEC COR 27 34 52 **Date Set:** 11/23/1976 **County:** Olmsted

Section: 27 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is at the surface
The corner falls in plum thicket on north side of open pasture
County Survey Disk in W side blazed 26" White Oak NNW 126.88'
County Survey Disk in NE side 24" blazed White Oak NW 143.38'
Post with sign NNW 2'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 27 and 34. 40.075 chs. Set a quarter section post. White Oak 16 in. N5ºW 15 lks. Elm 8 in. S44ºW 30 lks.

1-20-1874 Thomas Hunter (P. 238 No. 240), County Surveyor, found a stake. Checked it with the bearing trees. Drove a new stake.

10-1901 William Fraser (P. 25B), County Surveyor, found the stake and stumps of both bearing trees. Set a 11/2" x 10" x 20" stone and stake in place of the old stake.

2-1904 Charles Armstrong (P. 72B), County Surveyor, used the corner for work in Section 34.

11-23-1976 County Surveyor found Fraser's recorded stone. Set a CIM over a 1/2"x9" rod as the corner with the stone on the West side of the CIM.

4-18-2011 County survey crew found CIM in good condition.