Certificate of Location of Government Corner

ID#:522705 **Description:** SEC COR 27 28 33 34 52 **Date Set:** 5/4/2009 **County:** Olmsted

Section: 27 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls under E-W fence and 5' east of fence north
County Survey Disk in W side blazed 18" Black Oak NNE 75.7' (slope)
County Survey Disk in NW side blazed 11" White Oak NE 84.44' (slope)
Post w/sign 2' north
This corner is located by GPS reference stations "Horsman A & B"

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 33 and 34. 80.00 chs. Set post-corner to sections 27 & 28, 33 & 34 White Oak 15 in. N4ºE 30 lks. Burr Oak 7 in. N76ºW 12 lks. Aspen 8 in. S50ºE 33 lks. Aspen 8 in. S31ºW 23 lks.

1-1874 Thomas Hunter (P. 238 No. 240), County Surveyor, found the original stake and all the bearing trees which tested it correct.

4-1898 William Fraser (P. 621 No. 564), County Surveyor, found the remains of the old stake and tested it with the NE and the NW bearing trees and the SW bearing tree stump which proved it correct. Set a new stake with 2 long stones on the opposite sides of the stake.

10-1901 William Fraser (P. 25B) found stake and stone as the corner. Set a stake and 2 stones midway and on line at the 1/16th East.

2-1904 Charles Armstrong (P.72B), County Surveyor, found a stake with 2 stones.

11-24-1976 County Surveyor found a large limestone under the E-W fence. Doubled the line and measure from 1/4 corner 27-34 (found) over the 1/16th West (found) and the point came on the stone found. Set a CIM over a railroad spike as the corner with the stone on the south side of the CIM.

2-17-2009 County Surveyor found CIM up 0.1' leaning SE.

5-4-2009 County Surveyor removed leaning CIM and found RR spike down 1.3' in good condition. Removed RR spike and set 5' telspar pipe w/Cast Iron Cap up 0.1' at RR spike position. Set post w/sign.