Certificate of Location of Government Corner

ID#:522706 **Description:** 1/4 SEC COR 27 28 52 **Date Set:** 12/1/1976 **County:** Olmsted

Section: 27 **Township:** 105N **Range:** 12W **Monument Description:** Witness Corner:
Cast Iron Monument 15.0' North and on section line
This corner is located by GPS reference stations.

Reference Ties:

Witness Corner:
The witness corner falls 104' north of waters edge
County Survey Disk in N side 20" Elm W 75.09'
County Survey Disk in SE side Maple (clump) NE 29.75'
County Survey Disk in E side of the huge Maple (over corner) SSE 15.54'

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 27 and 28. 37.60 chs. Stream 20 lks. wide runs S.E. and enters prairie. 40.00 chs. W. Walnut 12 in. S51/2ºE 340 lks. Ash 10 in. S59ºW 50 lks.

7-1856 Thomas Hunter (Old field Bk. 13 P. 87), County Surveyor, used this corner.

5-1884 Thomas Hunter (Old field Bk. 14 P. 17), County Surveyor, set a stake from the SE bearing tree and the stump of the SW bearing tree.

4-1898 William Fraser (P. 621 No. 564), County Surveyor, reset the corner with a stake and 4"x6"x28" stone from the S.E. bearing tree found standing. Set a stake as a property corner 14.875 chs. South on the section line.

10-1901 William Fraser (P. 25B) found the corner P. 621.

11-30-1976 County Surveyor found a 3"x6"/9"x21" limestone set over a bottle at the property corner set by Fraser in 1898 at 14.875 chs. South.

12-1-1976 County Surveyor calculated the line and prorated Will Fraser measure from the SE Cor. 28 over Property corner found. The point came under a huge Maple. Dug on the East, West, and South sides of the tree but found no evidence of the corner. Accepted the calculated point as the corner location and set a CIM over a 11/4"x18" pipe as a witness corner 15.0' North and on line from1/4 Cor. 27-28 to Sec. Cor. 21-22-27-28.

7-22-2011 County survey crew found cast iron monument down 1.1' in good condition.