# Certificate of Location of Government Corner

**ID#:**522806 **Description:** 1/4 SEC COR 28 29 52 **Date Set:** 10/23/1989 **County:** Olmsted

**Section:** 28 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls 5 1/2' east of fence south 1' north of E-W fence
County Survey Disk in N side CP W 5.41'
County Survey Disk w/30d spike in E side 13" Cherry SSE 5.29'
County Survey Disk in W side brace post SW 10.37'
Sign on CP 5 1/2' west
This corner is located by GPS reference stations "Lone Cow A & B"

**Corner History:**

10-6-1853 Gov't Notes North between sections 28 & 29 VAR 11°35'E 40.00 set qr. section post 45.00 Enter day timber bottom E&W d150

7-1856 T. Hunter Pg. 12 No. 19 1/16 East 19.86 chs. then 9.93 chs. to 1/64 corner then 9.93 chs to center sec. Bearing trees to 1/16 corner (Black Oak 15" N261/4°W 20 lks.) (N 543/4°E 18 lks.)

12-1875 T. Hunter P. 288 No. 284 Found orig. stake standing. 4 lks. south of 8" forked white oak. 1/16 north set stake M&L and 7 woodlot stakes between.

9-1879 T. Hunter P. 363 No. 354 Stake had been moved 3' west. 1/16 west set stake M&L 20.09 chs..

4-1901 W. Fraser P. 2B Found remains of old stake 4 lks. south of white oak stumps. Set new stake with stone 1" x 9" x 14" by side. 1/16 west drove stake M&L 20.06 chs.

12-27-1976 County Surveyor dug small hole on north side of CP (found nothing).

10-20-1989 Land Consultants found stone.

10-23-1989 County Surveyor found stone. Dug out stone but found no evidence of stake. Set cast iron cap on telspar pipe at stone location.

6-30-2009 County Surveyor found cast iron cap on telspar pipe up 0.7' in good condition. Lowered pipe and reset cap up 0.3'.