Certificate of Location of Government Corner

ID#:523006 **Description:** W 1/4 SEC COR 30 52 **Date Set:** 8/20/1982 **County:** Olmsted

Section: 30 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road
Punch hole in N end CMP NE 34.12'
Punch hole in S end CMP SE 31.37'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor North between sections 25 and 30. 40.00 chs. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted SE Osage Orange and NE Apple seed.

9-23 to 25-1885 Thomas Hunter, County Surveyor, (Book A, Page 401, No. 391, and Old Fieldbook 14, Pages 49 and 50) "This 1/4 post also missing and no vestige of it could be found, nor could we learn of any one who knew or claimed to know where it had stood. We therefore as at D (W 1/4 corner 25) established it on line and midway (39.87 chs.) between the section corners G (SE corner 25--a stone set this survey) and A (NE corner 25--a stone set this survey) and set a stone at said point 24x9x3 inches which stone stands about 8 or 10 links south of the line of an old fence running East, but it could not be learned who built the said fence, nor if the 1/4 post was to be found when built or not." He used the corner to set the 1/16 North, a stone 22x6x3 inches, midway (19.93 1/2 chs.) and on line to the NE corner 25, and to set the 1/16 South, a 22x7x2 inch stone, midway (19.93 1/2 chs.) and on line to the SE corner 25. He also set the Center 25, a stone 20x0605 inches. At intersecting 1/4 lines. He set the 1/16 West, a stone not measure, on line and midway (19.96 chs.) the the Center 25, and the 1/16 West of the Center 25, a stake, on line and midway (20.04 chs.) between the Center 25 and the W 1/4 corner 25, a stone18x6x2 inches set this survey.

5-1973 County Surveyor found Hunter's recorded stone at the 1/16 South and found a stone set by William Fraser in 1894 (See Book A, Page 546, No. 506) at W Sec. corner 19-30. Also found Hunter's stone at the W 1/4 corner 25.

9-1977 County Surveyor dug at the W 1/4 corner 30 and the 1/16 North but could not find the corners set here by Hunter.

11-25-1980 County Surveyor found Hunter's recorded stone at the SE corner 25.

7-20-1982 County Surveyor found Hunter's recorded stone at the Center 25.

8-20-1982 County Surveyor set a Cast Iron Monument over a 3/4" rerod as the W 1/4 corner 30 at the intersection of the line from the W 1/4 corner 25 over the Center 25 and the line from the SE corner 25 to the NE corner 25. Hunter's stone at the 1/16 South falls on the line from the SE corner 25 to the NE corner 25.

7-10-2009 County Surveyor found CIM down 0.6' in good condition.