Certificate of Location of Government Corner

ID#:523104 **Description:** S 1/4 SEC COR 31 52 **Date Set:** 5/28/1981 **County:** Olmsted

Section: 31 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 10' north of centerline of E-W twp road and 1/2' east of fence north
Chisel cross in N end 30" culvert NE 11.42'
Chisel cross in W end 15" culvert NW 35.80'
Chisel cross in S end 30" culvert SSE 31.32'
This corner is located by GPS measurement

Corner History:

Gov't Notes 1853 Sept. West on so. boundary sect. 31 40.00 set qr. section post. Built mound with trench and drove charred stake in center. Gov't survey tie of 1.75 chs. w. to a stone 5"x11"x11" at No. 5-6 Jordan Twp. (Fillmore county)

9-1879 T. Hunter P.362 No. 353 Corner gone, set stake M&L 40 chs.

7-1917 J. Kerr Set 3/4" x 15" rod with bend in upper end and (?3" x 12" x 14") stone on top set M&L 2639.6 chs.

5-26-1981 Olmsted County Surveyor dug with backhoe from center line of E-W rd. to no. ditch, found J. Kerr iron with stone (3" x 12" x 14") above it .6' e. and 5.15' no. of the trav. nail. Did not dig further. Found T.H. stake hole with wood pieces running down 10" into clay 2.1'west & 5.75' north of trav. nail. Pulled J. Kerr iron but left stone to hold position. Set 1/2" iron in T.H. stake hole. Corner 10' no. of center line & in line of fence no.

5-28-1981 Olmsted County Surveyor set CIM over 1/2" rod at J. Kerr location.

11-10-2008 Olmsted County Surveyor found CIM down 0.7' in good condition.