Certificate of Location of Government Corner

ID#:523205 **Description:** S SEC COR 31 32 52 **Date Set:** 5/28/1981 **County:** Olmsted

Section: 32 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' south of centerline of E-W twp road and 19' east of centerline of N-S twp road
County Survey Disk in CP NW 59.95'
County Survey Disk in PP stub NNE 34.41'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes E. Norris, Deputy Surveyor West on South boundary of Section 32. 80.00 chs. Set post for corner to Sections 31 and 32. Black Oak 6" N50ºW 62 lks. Black Oak 6" N60ºE 90 lks.

9-1879 Thomas Hunter, County Surveyor, (Book A, Page 362, No. 353) "Found the original stake standing by side of fence, and also the N.W. witness tree - the others gone. Tested stake and found it correct per U.S. Field Notes." He used this corner to set the S. 1/4 Cor. 31, a stake, midway (40 chs.) to the S.W. Cor. 31.

10-1899 O.H. Case calls for this corner in the plat of Judicial Road located in Fillmore and Olmsted Counties.

7-1917 John Kerr, Olmsted County Surveyor, (Kerr Book - 10, Page 27-29) "Found part of old stake and hole where iron stake had been pulled out which distance corresponds with the records by Hunter and also corresponds with old fence line on N. side of road." He set a 3/8" rod 2.7' long with eye on top end in the old hole and set stone on top of it. Measured West 5279.2'. Used this corner to set S. 1/4 Cor. 31 midway and on line to the Twp. Cor.

5-27-1981 Olmsted County Surveyor dug and found Kerr's iron with stone above along side stake hole. Iron packed in small rock.

5-28-1981 Olmsted County Surveyor set a CIM over a 1/2" iron over the corner found 5-27-1981.

11-10-2008 Olmsted County Surveyor found CIM down 1.2' in good condition.