Certificate of Location of Government Corner

ID#:523206 **Description:** 1/4 SEC COR 31 32 52 **Date Set:** 3/17/2009 **County:** Olmsted

Section: 32 **Township:** 105N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 5' south of fence west and 1' west of centerline N-S twp road
Punch mark in E end 36" CMP NE 22.63'
County Survey Disk in PP #13541 SW 64.02'
This corner is located by GPS reference stations "Kohlmeyer & Allis"

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between Sections 31 and 32. 40.00 chs. Set quarter section post in grubby land. Made mound, deposited charred stake, dug trench and pits and planted Cherry seeds NE and SW.

9-1879 Thomas Hunter, County Surveyor, (Book A, Page 362, No. 353) "Found remains of old stake in center of road, considerably below the surface. Set stone 18"x11"x2" with broken stones around bottom and also set old stake found, by side of stone." He used this corner to set the 1/16 West, the Center 31, and the 1/16 West of the Center 31.

7-1917 John Kerr, County Surveyor, (Kerr Book - 10, Page 27-29) measured East line of Section 31 and set a point (no description) midway (2637.6) and on line between the section corners. Measured West on E-W 1/4 line Sec. 31.

5-27-1981 County Surveyor dug and found Hunter's stone 2"x11"x18" packed in small limestones 10' deep in N-S crushed rock road. Put junk around with 3/4" conduit on East side.

6-11-1981 County Surveyor set a Cast Iron Monument over a 1/2" rod over the stone found 5-27-1981.

11-5-2008 County Surveyor visited area and found CIM destroyed due to culvert work.

3-17-2009 County Surveyor set a 1" x 18" square pipe w/cap down 0.5' from GPS coordinates.