Certificate of Location of Government Corner

ID#:523305 **Description:** S SEC COR 32 33 52 **Date Set:** 4/20/2011 **County:** Olmsted

Section: 33 **Township:** 105N **Range:** 12W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is down 0.5'
The corner falls in centerline of CR 138, in line with fence north and 42 1/2' east of fence south
County Survey Disk in PP #13496 NNE 36.48'
This corner is located by GPS reference stations "Pt Near 420408 & Y"

Corner History:

9-1853 Gov't Notes West on south boundary of sect. 33. 80.00 Set post for corner to sections 32 and 33.
Blk. Oak 8 in. N75E 14 lks. White Oak 10 in. N89W 42 lks.

9-1881 T. Hunter (Book 5, P. 125) 1/16 N 19.93 1/2 chs. M&L 1/16 west M&L 19.88 chs.

11-17-1994 County Surveyor set cast iron cap on telspar pipe in centerline CR 138 on line for 2 miles. East-West and in line of fence north.

11-5-2008 County survey crew found cast iron cap on telspar pipe down 0.4' leaning west and removed.

4-20-2011 Olmsted County survey crew set a 4' telspar pipe with cast iron cap from computed coordinates of 1994 location.

7-21-2011 Olmsted County survey crew found CIC down 0.4 in good condition.