Certificate of Location of Government Corner

ID#: 523309 **Description:** SEC CEN 33 52 **Date Set:** **County:** Olmsted

Section: 33 **Township:** 105N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1/2" pipe

Reference Ties:

The corner falls 8' west of north-south fence and 13' south of fence west
The monument is at the surface
This corner is located by GPS measurement

Corner History:

4-6-1885 Thomas Hunter, County Surveyor, (Book A, Page 395, Survey No. 385) found, accepted and used marked stake set by S. Freeman. 1/16th West this corner comes in creek midway and on line at 19.83 chains (1308.78'). Set witness corner 2 rods (33.00') north.

2-24-1904 Charles Armstrong, County Surveyor, (Book B, Pages 72-73) shows stake.

8-23-2005 GGG found monument, but used computed center at intersecting quarter lines.

4-20-2011 County Survey Crew found 1/2" pipe at surface in good condition and measured its position using GPS.

8-29-2012 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the 1/2" pipe, as located by GPS in 2011, falls 1.03' south and 0.01' west of the computed center.