Certificate of Location of Government Corner

ID#:523406 **Description:** 1/4 SEC COR 33 34 52 **Date Set:** 8/29/1979 **County:** Olmsted

Section: 34 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 0.1'
The corner falls 5' N of corner post and in line with fence south and 2' south of fence east.
Center 8" Elm NE 4 1/2'
Center 6" Walnut SW 59.7'
Sign on corner post south 5'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 33 and 34. 40.00 chs. Set quarter section post. White Oak 16 in. S761/2E 55 lks. White Oak 15 in. N24W 22 lks.

1-1874 Thomas Hunter, County Surveyor, (Book A, Page 238, No. 240 and Old Field Book 3, Pages 71-72) "Found the stake standing (not the original) and also both witness trees. Tested it by U.S. Field notes, found it one link out of the way. Set new stake properly marked. The Bearing and distance of the SE witness tree is correct and the distance to the NW tree is also correct but the bearing is N33°W instead of N24°W as per field notes." He set a stake not marked 20 chains East on the old blazed line (he found old stakes on the line). He marked a 6" Jack Oak as the 1/16th North.

2-1904 C.H. Armstrong, County Surveyor, (Book B, Page 72) set an oak stake 3" square and 2' long as the corner midway and on line between Sec. Cor. 27-28-33-34 and a point 60 lks. East of a point (1 rod East and 2 rods North of a fence corner as set by a Mr. Murphy) assumed as the N. 1/4 Cor. 3, 104-12. From his midway and on line location he searched for old Bearing trees: "I find two stumps that correspond in measurement but not in course and as they are about 12 lks. From where point falls for corner, I ignore them as not being good evidence." He set an oak post 3" square and 3' long for the Center 34 midway between 1/4 Cor. 33-34 as set and a straight line between the NE Cor. 34 and the SE Cor. 34, and on line from the 1/4 Cor. 33-34 as set to 1/4 Cor. 34-35 which he found. He also set a stake 3" square midway and on line at the 1/16th East of the Center 34 and an oak stake at the 1/16th West of the Center 34.

8-7-1979 County Surveyor, at the 1/16th East of the Center 34, found a 31/2"x31/2"x2' limestone standing on the SW side of the corner post to fences E-W-N. Dug and found the remaining 12" of a small post or stake of 3" to 4" diameter appx. 2' deep and 1.3' East and .45' South of the center of the stone.

8-17-1979 County Surveyor dug at the Center 34 but did not find anything. Also dug at 1/4 Cor. 33-34. Found only the stub of an old post on the NW side of the corner post in place.

8-29-1979 County Surveyor dug again at 1/4 Cor. 33-34 but found nothing further. Set a Cast Iron Cap on a square pipe as the corner in line with the fence South and on line from the E. 1/4 Cor. 34 over the stake found at the 1/16th East of the Center 34.

4-18-2011 County survey crew found cast iron cap on square pipe in good condition.