Certificate of Location of Government Corner

ID#:523504 **Description:** S 1/4 SEC COR 35 52 **Date Set:** 4/8/2011 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 12W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is down 0.1'
The corner falls 32' east of CP to fences N-S-E-W
County Survey Disk in N side 27" Maple NW 34.93'
County Survey Disk in E side 4" blazed Maple SSW 38.98'
Post with sign south 1.5'
This corner is located by GPS reference stations 523504A and 523504B

Corner History:

9-1853 Gov't Notes E. Norris, Deputy Surveyor West on south boundary of section 35. 40.00 chs. Set quarter section post. Linn 14 in. N70ºW 13 lks. White Oak 14 in. N57ºE 64 lks. 40.11 chs. Linn 15 in.

10-1895 O.H. Case, Fillmore County Surveyor, (P. 110 Fillmore County Records) records an iron at this corner.

2-1902 William Fraser (Book B P. 30), County Surveyor, found the iron stake set by the Fillmore County Surveyor.

8-9-1978 Olmsted County Surveyor found a 2 1/2" square iron (up 8") under the E-W fence. Set a survey marker sign .8' South.

1-4-1994 Jerome Schwarz found and used square iron bar as corner for survey in SW 1/4 section 35.

4-8-2011 Olmsted County survey crew found 2 1/2" square iron bar up 0.6' leaning north and slightly east. Removed iron bar and set 5' telspar pipe with cast iron cap using nail ties in trees which were set in 1978 (Maple tree NW 34.93' and Maple tree SSW 38.98') Delivered the sq. iron bar to the Fillmore County Surveyor.