Certificate of Location of Government Corner

ID#: 523505 **Description:** S SEC COR 34 35 52 **Date Set:** 10/1895 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 12W **Monument Description:** 1 1/2" x 2 3/4" topped iron

Reference Ties:

The monument is down 0.7'
The corner falls 10' west of centerline of N-S twp road and in line with fence west
Spike in N side PP #13692 WNW 20.71'
Spike in top of brace post WSW 19.35'
Spike in top of fence post SW 26.9'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes E. Norris, Deputy Surveyor West on south boundary of section 35. 80.00 chs. Set post for corner to sections 34 and 35. Black Oak 10 in. N42ºW 52 lks. White Oak 20 in. N60ºE 66 lks.

10-1895 O.H. Case, Fillmore County Surveyor, records an iron at this corner.

2-1902 William Fraser, County Surveyor, (Book B P. 30) found an iron set by the Fillmore County Surveyor.

9-25-1975 Fillmore County Surveyor found a 1 1/2" x 2 1/2" x 30" solid iron bar. Fillmore County Certificate of Location Doc. No. 373483

7-28-1978 Olmsted County Surveyor found a 1 1/2" x 2 3/4" iron down 0.5' in the road and 7' West of the center of the road north and south. The corner is in line with the fence west.

1-4-1994 Jerome Schwarz found and used iron bar as corner for survey in SW 1/4 section 35.

4-7-2011 Olmsted County survey crew found 1 1/2" x 2 3/4" iron bar in good condition.