Certificate of Location of Government Corner

ID#:523605 **Description:** S SEC COR 35 36 52 **Date Set:** 3/14/2005 **County:** Olmsted

Section: 36 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 3' west of N-S fence and 1' south of fence west
County Survey Disk in E side 8" Maple N 21.60'
Spike in NW side 10" Maple NE 19.80'
County Survey Disk in S side tree E 2.31'
Post w/sign 1' north
This corner is located by GPS reference stations "Finley A & B"

Corner History:

9-1853 Gov't Notes E. Norris, Deputy Surveyor West on south boundary of section 36. 80.00 chs. Set post for corner to sections 35 and 36. White Oak 14 in. N42ºW 16 lks. White Oak 20 in. N62ºE 37 lks.

10-1895 O.H. Case, Fillmore County Surveyor, (P. 109 of Fillmore County Records) ran North from the Center 1, T104, R12W (which he set) and "at 39.72' Intersect County line at old corner where I plant iron post for 1/4 section corner."

8-7-1978 Olmsted County Surveyor, A Mr. Green, a former land owner at the corner, told the Fillmore County Surveyor he had broken the iron off and the remainder was about 1' deep along side a big tree used as a corner post. We dug on the West side of a 27" Red Oak used as the corner post to fences N-S-E-W and found a 1 1/2" x 2 1/2" topped iron down 1'. Set a CIM over the iron.

2-25-2005 Olmsted County Surveyor found CIM leaning NE down 0.2'. Took local ties and removed. Found 1 1/2x3" iron tractor hitch down 2.0'. Checked iron against ties in trees CSD in east side of 8" Maple 21.75' and spike in NW side of 10" Maple NE 19.92'.

3-14-2005 Olmsted County Surveyor removed iron and set 5' telspar w/CIC up 0.3' from computed coordinates. CSD in east side of 8" Maple north 21.60' and spike, partially covered by tree in NW side 10" Maple NE 19.80'. CSD w/conc. Nail in south side of tree used as corner post east 2.31'. 7" White Oak down.