# Certificate of Location of Government Corner

**ID#:** 530109 **Description:** SEC CEN 1 53 **Date Set:** 7/7/1969 **County:** Olmsted

**Section:** 01 **Township:** 105N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the monumented center of section.

Cast Iron Monument

**Reference Ties:**

The corner falls 9' south of fence east and 3' west of north-south fence
The monument is down 0.6'
Hard nail in south side brace post ENE 3.0'
Center of corner post to fences north-south-east NNE 9.8'
This corner is located by GPS measurement

**Corner History:**

7-14-1876 Thomas Hunter, County Surveyor, (Book A, Page 301, Survey No. 296) set stake at intersecting quarter lines. Set stake deep even with ground surface. 1/16th East set stake midway and on line at 19.89 chains (1312.74') to East 1/4.

6-23-1969 John Kerr dug and found stone found by Ken McGhie 1.5' west of corner post. The stone had a flat base pointed up and ran down to a point at the bottom. No records of stone being set. Found nothing further.

7-3-1969 John Kerr, County Surveyor, set Cast Iron Monument 1' west of stone found by Ken McGhie. Set old stone point up on east side and 2"x8"x16" limestone on west side with broken glass jug around corner.

7-7-1969 John Kerr, County Surveyor, took additional measurements in section 1 and computed the center of section. Reset Cast Iron Monument 9.62' south over 1"x12" rod with boulder on east side and limestone on west side at the computed center. RP - hard nail on south side 7" round oak brace post ENE 3.0', center corner post (8" oak) fences E-N-S NNE 9.8'.

12-23-1976 County Survey Crew found Cast Iron Monument.

6-1-1995 Jack Rother found and used monument.

2-25-2011 County Survey Crew found Cast Iron Monument down 0.6' in good condition and measured its position using GPS.

3-2-2011 Joel Thoreson, County Surveyor, recommends using the monumented center of section based on historical use of this position.

7-30-2018 MnDOT found and used Cast Iron Monument for Minnesota Department of Transportation Right of Way Plat No. 55-117.