Certificate of Location of Government Corner

ID#:530404 **Description:** 1/4 SEC COR 4 9 53 **Date Set:** 8/8/1969 **County:** Olmsted

Section: 04 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 7' east of N-S fence
Center huge Boxelder SE 54.7'
Juniper Cedar 6' high in fence S 96.0'
Post w/sign 1' west
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes Michael Karrick, Deputy Surveyor West on true line between sections 4 and 9. 40 chs. Set quarter section post. Burr Oak 8 in. N15°E 43 links Burr Oak 10 in. S73°E 436 links 80.00 chs. Section Corner.

5-1856 Thomas Hunter, County Surveyor, (Book A, Page 5, No. 8) used this corner to set the Center 9.

5-1874 Hunter (Book A, Page 248, No. 249 and Old Field Book 3, Pages 93-94) found the stub of the old stake. Set stone 22"x17"x1-1/2" in its place.

5-1900 Robert Fraser, Deputy County Surveyor, (Book A, Page 676, No. 601 and Old Field Book 15, Pages 65-66) "found stone as described in previous survey and a little stone on top."

7-1907 C. Armstrong, County Surveyor, (Book B, Page 112) found stone 17" x 24"x2-1/2". Set limestone 30"x8"x2" on North side of stone as found.

8-7-1969 John Kerr, County Surveyor, (Cert. Filed, Card, and Kerr book 98, Page 77) found two limestones as recorded. Set a Cast Iron Monument between the stones. The corner is 2' East of the N-S fence.

1971 County Surveyor found Kerr's CIM.

1976 County Surveyor found Kerr's CIM.

4-22-1980 County Surveyor set a survey marker sign and post 1.1 West of Kerr's CIM.

12-26-2002 County Surveyor found CIM down 0.8' in good condition.