# Certificate of Location of Government Corner

**ID#:** 530405 **Description:** SEC COR 4 5 8 9 53 **Date Set:** 11/7/1969 **County:** Olmsted

**Section:** 04 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

**Reference Ties:**

The corner falls 21' south of east-west fence and in line with fence west
The monument is down 0.6'
Sign in fence post 3' west
County Highway Disc in 20" Oak S 17.16'
Bottle cap in fence post SW 3.13'
This corner is located by GPS measurement

**Corner History:**

5-22-1854 Michael G. Karrick, Deputy Surveyor, measured north 80.00 chains between Sections 8 and 9. Set post in mound with trench, pits, charred stake for corner to Sections 4, 5, 8 & 9. Planted Osage Orange seeds at each angle.

4-11-1856 Thomas Hunter, (Book A, Page 2, Survey No. 3), shows section corner. 1/16th West set midway and online at 20.12 chains (1327.92').

7-12-1856 Thomas Hunter, (Book A, Page 13, Survey No. 21), shows section corner. 1/16th West set midway and online at 20.12 chains (1327.92').

5-21-1874 Thomas Hunter, County Surveyor, (Book A, Page 248, Survey No. 249), found remains of old stake. Set 2"x6"20" stone in its place. The corner falls at the intersection of fences east, west and south. 1/16th East set staked midway and online at 20.09-1/2 chains (1326.27').

7-12-1907 Charles Armstrong, County Surveyor, (Book B, Pages 112-113), found 2"x7" limestone. The corner is in line and aboout 20' south of corner post to fences north and west.

1960 Minnesota Highway Department found 2"x6"x20" stone. The corner falls south of fence corner. RPs - Disc in fence post N 8.8', Disc in fence post NE 32.6', Disc in Oak S 17.3'.

7-30-1969 John Kerr, County Surveyor, (Kerr Field Book No. 98, Page 76), found 3"x7"x12" stone. Set Cast Iron Monument over 5/8"x12" rod with stone by side. The corner falls 20' south of east-west fence. RPs - Disc in fence post N 8.6', Disc in fence post NE 32.3', Disc in Oak S 17.15'.

3-1-2006 County Survey Crew found Cast Iron Monument down 0.6' in good condition and measured its position using GPS. The corner falls 21' south of east-west fence and in line with fence west. Sign in fence post 3' west. RPs - County Highway Disc in 20" Oak S 17.16', Bottle cap in fence post SW 3.13'.