Certificate of Location of Government Corner

ID#:530409 **Description:** SEC CEN 4 53 **Date Set:** 5/2/2007 **County:** Olmsted

Section: 04 **Township:** 105N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 4' north of centerline of CSAH 16
Ref pipe S 69.98'
This corner is located by GPS measurement

Corner History:

7-1907 Charles Armstrong, County Surveyor, (Book B, Page 112) set a stone 2-1/2"x11"x36" at intersecting 1/4 lines.

9-24-1971 County Surveyor dug and found Armstrong's stone. Set a 1"x22" pipe over the stone.

4-30-1980 County Surveyor set a 1"x35" square pipe with cap as the Center 4 at intersection 1/4 lines.
Note: The 1" square pipe would be 3.7 North and 3.6 East (by 1976 electronic traverse comp.) of the pipe over Armstrong's stone. When Armstrong set his stone he had incorrectly set the W. 1/4 Cor. 4 midway and one line between the section corners and was also probably using a different N 1/4 Cor. 4 than the corner being used today.

5-1-1980 Yaggy Associates set 3/4" pipe w/cap RLS #10162.

6-21-1995 County Surveyor found 1" square pipe w/cap 4' North of centerline CSAH 16. Set 1" square pipe w/cap 65 1/2' South of centerline CSAH 16 10' West of fence line South top angle ref pipe. Left angle RT P.K. in PP #47339 (1st pole W on N side CSAH 16) to center 4 57° 48' 06.5" to center 4 VA 91° 25' 39" dv 07 slope 69.995 hor 69.975.

9-20-1995 county highway department set 1" square pipe w/cap at surface from 1995 overlay tie out.

5-2-2007 County Surveyor found 1" square pipe w/bad cap. Removed the 1' pipe and set a 1"x2' pipe w/cap at old pipe location.