Certificate of Location of Government Corner

ID#:530704 **Description:** 1/4 SEC COR 7 18 53 **Date Set:** 4/17/1973 **County:** Olmsted

Section: 07 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4 1/2' north of centerline of E-W twp road
Spud in N side PP #9694 WSW 96.44'
Bottle cap in W side Oak CP S 36.6'
Bottle cap in E side cresoted CP N 30.26'
This corner is located by GPS measurement

Corner History:

Gov't Notes: M.G. Karrick West random 7 & 18 40.00 set temp 1/4 section post East on true line between section 7 & 18 39.80 set 1/4 section post in mound with trench, pitts, and charred stake and Osage Orange seeds N.E. & S.W.

6-1886 T. Hunter (P411 No. 400) found stone in center road placed by pioneer. Mr. Hare and others to replace original stake, never disputed. 1/16 South set stake M & L 20.02. N55'E.

6-1892 W. Fraser (P502 No.472) used corner projecting line over center 7 to replace 1/4 Cor. 6-7.

10-1961 J. Kerr found stone while surveying tabaccy road farm. Found 12" square by 3' limestone broke off part, placed CIM on top bal. Center Burr Oak just West of fence N 212.0

4-17-1973 County Surveyor went to corner to run & meas line South. Found road had been graded and C.I.M. 2.3' below surface. Placed another CIM on top and re-referenced. 96.44 WSW to original spud pulled and raised 3' on N side either different PP or re-numbered C.B. 45 and 9694. 36.6 S to bottle cap on W side old oak corner post. 29.49 N to bottle cap on E side cresoted corner post. Meas South to original CIM set as center 18 8-1964 2641.96. Meas South to 1" rod set NE corner stone found 2636.91. Center 18 as reset 5.73 short of record. Center 18 South 6.44 short of record.

6-20-2005 County Surveyor found CIM down 0.5' in good condition.