Certificate of Location of Government Corner

ID#: 530709 **Description:** SEC CEN 7 53 **Date Set:** 9/29/1971 **County:** Olmsted

Section: 07 **Township:** 105N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Cast Iron Monument

Reference Ties:

The corner falls in center line of east-west field drive
The monument is down 0.5'
Bottle cap in W side CP S 34.2'
Post w/sign 10' north
This corner is located by GPS measurement

Corner History:

6-1892 William Fraser, (Book A, Pages 502-503, Survey No. 472) found and used stake set by Hunter.

4-17-1905 Robert Fraser, (Book B, Pages 84-85) found and used stone. 1/16th West set long thin stone on line at proportionate government distance at 19.90-3/4 chains (1313.90') then 19.60-3/4 chains (1294.10') to West 1/4. 1/16th Center of NW 1/4 found and used stake and stone set by Charles Armstrong.

5-1917 Charles Armstrong, (Book K, Page 19) used center.

1942 County Highway Department assumed corner and set 5/8" rod.

7-29-1964 John Kerr, County Surveyor, found rod. Dug and found nothing further. Accepted rod and set Cast Iron Monument over rod. The corner falls 1-1/2' south of center line of east-west road and in line with fence south. RPs - Chiseled "+" in south end 24" CMP SE 28.3', Chiseled "+" in north end 24" CMP NE 31.05', MHD disc in corner post S 42.7'.

9-29-1971 Roger Brand, County Surveyor, dug and found recorded 4"x7"x20" limestone down 4.3'. The stone falls 0.95' west and 0.55' south of County Highway Department's assumed position. Set Cast Iron Monument over 5/8" rod over stone. RP - Bottle cap in west side CP S 34.2'.

NOTE: THIS IS A CORRECTION OF A CORNER. SEE ENTRY FOR 9-29-1971.

10-14-1998 GGG found and used monument.

6-27-2005 Vince Fangman found and used Cast Iron Monument.

9-15-2006 County Survey Crew found Cast Iron Monument down 0.5' in good condition. Set post w/sign.

5-2-2007 County Survey Crew found Cast Iron Monument down 0.5' in good condition and measured its position using GPS.

12-29-2008 Vince Fangman found and used Cast Iron Monument.

4-21-2014 Joel Thoreson, County Surveyor, recommends using the monumented center of section based on historical use of this position.

11-7-2014 McGhie & Betts, Inc. / WSB used Cast Iron Monument position as center of section.