Certificate of Location of Government Corner

ID#:530806 **Description:** 1/4 SEC COR 7 8 53 **Date Set:** 7/29/1964 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in line with farmyard fence north
Natural blaze in E side east twin 6" Pines SSW 46.9'
Stone cornerpiece of Northeast corner brick house SE 128.5'
County Survey Disk in E side PP #45402 SSW 46.47'
County highway disk in PP SE 159.62'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: M.G. Karrick. 40.00 set 1/4 section post in mound with trench, pitts, and charred stake and Osage Orange seeds NE and SW.

11-1912 D. Williams (P.188B) found limestone Mon as corner (origin unknown). Meas East to E 1/4 8 2676 M & L or 5352' cemetery layout (see center section 8).

5-1917 Chas Armstong (book K page 19) plat shows stone. Meas West 39.42. (2601.72'). Meas North 19.96 or 39.96 1317.36 or 2637.36.

7-29-1964 J. Kerr found stone with rod riser used in many surveys and referenced. Set CIM over stone. RP's: Corner lies in line farmyard fence running North to natural blaze on East side of Easterly of Twin Pines SSW 63.0. MHD disc in top fence post N 40.0. Sp in power pole SSW 46.9. Disc in power pole SE 159.62. Sp in tele pole NE 90.32. Stone cornerpiece of NE corner brick house SE 128.5.

12-10-2002 County Surveyor found CIM down 0.7' in good condition.

6-20-2005 County Surveyor found CIM down 0.7' in good condition.