Certificate of Location of Government Corner

ID#: 530809 **Description:** SEC CEN 8 53 **Date Set:** **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

This corner is located by GPS reference stations "Law A & B"

Corner History:

4-11-1856 Thomas Hunter, (Book A, Page 2, Survey No. 3) set stake at intersecting quarter lines. 1/16th North set stake midway and on line at 19.80 chains (1306.80') to North 1/4. 1/16th East set stake midway and on line at 20.25 chains (1336.50') to East 1/4. 1/16th Center of NE 1/4 set stake midway and on line at 19.82 chains (1308.12') on north-south sixteenth line.

5-14-1856 Thomas Hunter, (Book A, Page 5, Survey No. 8) found stake. 1/16th South set stake midway and on line at 19.85 chains (1310.10') to South 1/4. 1/16th East found stake. 1/16th Center of SE 1/4 set stake midway and on line at 20.27 chains (1337.82') on east-west sixteenth line.

11-25-1912 D. Williams, (Book B, Page 188-189) set center midway and on line at 2676' on east-west quarter line.

11-4-1921 County Highway Department, (C.H.D. Book #35, Page 3) set hub at an assumed corner. P.I. Sta. 479+58.2. RPs - North end 24" RCP-Arch culvert NE 59', South end 24" RCP-Arch culvert SE 58.5'.

9-29-1971 Roger Brand, County Surveyor, measured east-west quarter line. Total distance 5358.85'.

3-10-1999 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

12-10-2002 County Survey Crew visited area of corner and found nothing.

10-13-2005 Ramaker & Associates found and used PK nail.

3-14-2007 Ed Kuisle, County Surveyor, used computed center at intersecting quarter lines for Olmsted County Highway Right of Way Plat No. 167 & No. 168.

10-5-2018 SEH used computed center at intersecting quarter lines.