Certificate of Location of Government Corner

ID#:530906 **Description:** 1/4 SEC COR 8 9 53 **Date Set:** 9/29/1971 **County:** Olmsted

Section: 09 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of centerline of E-W twp road and 4' east of fence north
W nail in No. plate of PP #17503 WSW 91.03'
Bottle cap in S side PP #17504 ESE 146.12'
Bottle cap in E side CP NNW 51.3'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes M.G. Karrick. 40.00 set 1/4 section post in mound with trench and charred stake and Osage Orange seeds NE & SW. 48.90 Wagon Road W.W.

4-1856 T. Hunter (Pg.2 No.3) shows 1/4 post 1/16 West 20.25 chs. M & L.

5-1856 T. Hunter (Pg.5 No.8) shows 1/4 post. 1/16 West 20.25 chs. M & L to center sec. 8. 1/16 East 20.02 chs. M & L to center sec. 9. 1/16 South 19.91 chs. M & L to sec. Cor.

1874 T. Hunter (Bk. A pg. 248) found the remains of the old stake - set stone

9-1886 T. Hunter (P.415 No.404) found stone (P.248) center of road. 1/16 East set cedar stake M & L 20.05 1323.3 N. 89 3/4°E. 1/16 South found old stake M & L 19.94 1/2 1316.37 S 1/2°E. 1/16 center SW 1/4 9 set stake M & L on E-W 1/16 line 20.10 M & L also set stake 2.50 chs. East of above 1/16 on line for line South.

1912 D. Williams (Bk. B pg. 188) found a stone in the center of the road. To search for corner set line from 1/4 7-8 over line 37' South of cemetery which is 181.5 N & S and 206.25 E & W the NE cor being 37' S and 132' W of center 8.

8-8-1969 J. Kerr run line as above no Meas as yet, set 1/2" rod in road came 2' + S centerline road. 43.8 NW to center tele. Pole 87.1 WSW to West tack in no plate power pole 1750.3-corner may come West.

9-21-1971 County Surveyor measured from 1/4 7-8 CIM East, found 1/16 fence North at 1342.75, West side cemetery fence at 2350.7. Set nail at 2565 about East side cemetery. Set nail at 2676 on transit line came 16.5' W centerline blacktop. Con't meas East found fence running N on East side road at 1275.15 or 3951.15. Found rod set 8-1969 at 2682.85 or total mile 5358.85. Used this rod as E end line.

9-29-1971 County Surveyor found the stone - bottom 12" of recorded 2"x12"x22" stone and placed cast iron monu. Over the stone. RPs- The corner lies 2' South of the center of the road running south and 4' east of the fence running N, 91.03' WSW to the W nail in the No. plate 17503 of the P.P., 146.12' ESE to a bottle cap on the S side of PP #17504, 51.3' 4' W of N to a bottle cap on the E side of a corner post, 85' E to the line of newly planted evergreen trees running S.

11-27-2002 County Surveyor found CIM down 0.5' in good condition.

5-23-2006 County Surveyor found CIM down 0.6' in good condition.