Certificate of Location of Government Corner

ID#:531004 **Description:** 1/4 SEC COR 10 15 53 **Date Set:** 8/5/2011 **County:** Olmsted

Section: 10 **Township:** 105N **Range:** 13W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is up 0.2'
1 1/2' west of eyeball line of pole line south
This corner is located by GPS reference stations "BVP A & B"

Corner History:

1854 Gov't Notes M.G. Karrick East random 10 & 15. 40.00 set temp 1/4 section post West on line between section 10 & 15. 40.00 set 1/4 section post 10" 15'. Aspen 9 N67 W22. Aspen 7 S85 E27.

1-1858 T. Hunter (Pg.46 No.68) shows 1/4 post meas North 10 chs. Then 20 ch then 10chs to cen sec 10 meas East 10 chs then 10 chs then 20 chs to sec corner (see survey for breakdown & B.T.s to 1/16 corners).

1-17-1876 T. Hunter fieldbook No.4 used a point North for wood lot line West still prop line at 8.75 577.5 A witness tree to this point 3" ash N 42 1/2 E 8 lks. 5.28' market B.T. at root and other unreadable markings. Also prop line East still used at 10 chs 660'.

6-1886 T. Hunter (P410 No.399) found old stake lying on ground and stub in ground tested stumps of bearing trees. Set new stake with old stake and iron stake by its side. 1/16 West set stone with stake by side M & L 19.94 1/2 line South. (1316.37)

2-1892 Thos. Fraser (P470 No.451) found iron stake in rock on SW side of hill by Hunter. Used to set center 10 only. No measure.

1-1894 W. Fraser (P543 No.504) found iron stake P470. Set stone 2 x 12 x 20 M & L 19.77 at 1/16 corner South. BT 6" Hickory N 81 1/2 E 18 lks. (1304.82)

5-1921 Chas. Armstrong (book B. Page 53) shows iron as 1/4 corner with B.T. S N 82 1/2 E 26 chs. 17.16 N 6 1/2 W 23 chs. 15.18 N 0° 40' W to center 10 (see center 10).

5-12-1972 County Surveyor measured from NE 15 West. Found iron in fence at 657 ± very rugged & brushy. Found 4" X 4" post at 1226±. Found small stone N side fence at 1316.65. Found fence South at 1482 definate prop line. Sound fence North at 1650. Found 1" x 16" iron at 2620.2. Meas West to stone in flood plain 9-10-15-16. Meas uncertain line uncertain searched extensively for 1/16 stone between 1/4 10-15 and 9-10-15-16 set 6-1886. M & L 19.94 1/2 1316.37 this area quite steep and washed.

5-17-1972 County Surveyor ran N-S 1/4 line 15 from CIM set at 1/4 15-22 where positive stone found 5-17-72 over positive L stone at center. Con't elect line from 1/4 15-22 on 10' E over center 15 on 10' E to E-W fence at 1/4 10-15. Found meas to be 1328 not 1304.82 record. Set dragtooth in rock hillside 21.8 S of zap nail.

5-30-1972 County Surveyor reset iron dragtooth on exact line from South 1.51 N or 2609.64 North of center 15 believe this final corner unless electronic traverse line taken and used dip needle to search again for iron very likely removed. Dragtooth 11.25 West of 1" pipe found about 22 +' South 1.7 West of eyeball line of pole line South. 8.4 SW to center 8" Oak stump (sort of hidden corner)

1-22-1985 McGhie & Betts found dragtooth. Measured 2629.84 to SE corner 10. Surveyed SE 1/4 SE 1/4 sec 10.

6-6-1988 V. Fangman used dragtooth inside 1/2" x 18" pipe for survey in SW 1/4 section 10.
1-10-2002 V. Fangman used dragtooth inside 1/2" x 18" pipe for survey in SW 1/4 section 10.

10-5-2004 County Surveyor found 5/8" pipe w/undistinguishable plastic cap up 0.2' belived to be 1/4 corner. Did not find stump or 1" pipe. Removed pipe and used magnetic locater, did not find anything, reset pipe in original hole.

3-12-2008 QED Engineering Inc. found and used 5/8" pipe at quarter section corner.

8-5-2011 County survey crew found 5/8" pipe in good condition. Set 4' telspar pipe with cast iron cap over pipe.