Certificate of Location of Government Corner

ID#:531005 **Description:** SEC COR 9 10 15 16 53 **Date Set:** 12/12/2002 **County:** Olmsted

Section: 10 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

8" Hackberry tree N 13'
18" twin Elm ESE 21'
White steel post 2' west
Post w/sign 2' north
This corner is located by GPS reference stations "Bennett & DW A"

Corner History:

1854 Gov't Notes M.G. Karrick, Deputy Surveyor North between sections 15 and 16. 80.00 chs. Set section corner post. Sugar 11 in. S41°W 85 lks. Hackberry 12 in. N24°W 55 lks. Elm 13 in. N34°E 45 lks. Walnut 8 in. S58°E 38 lks.

1-1864 P.C. Compton (Pg79 No.118) shows section corner used to set 1/16 South to subdivide SE 1/4 of NE 1/4 of sec 16.

9-1876 Thomas Hunter (p.305 No.300), County Surveyor, states original stake gone, but all bearing trees or stumps standing and plainly marked. Set a new stake deep to protect from river overflow.

6-1886 T. Hunter (p.410 No. 399) found stake and set a boulder with cross in center and section numbers chiseled in respective corners.

11-1886 T. Hunter (P.417 No.406) found stone.

2-1892 Thomas Fraser (p.470 No.451) found stone.

11-1902 Charles Armstrong, County Surveyor shows stone at corner on plat.

4-6-1972 County Surveyor found recorded stone with cross and section numbers in respective corner. Drove a 3/4" rod on west side of stone up 18" and drove a steel fence post on north side.

12-12-2002 County Surveyor found 3/4 iron rod, removed stone and set 4' telspar with CIC over iron rod up 0.4'. Set sign & post 2' North and white post 2' West.