Certificate of Location of Government Corner

ID#:531006 **Description:** 1/4 SEC COR 9 10 53 **Date Set:** 4/28/1980 **County:** Olmsted

Section: 10 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Cap on a telspar pipe

Reference Ties:

The corner falls 3' west of bulkhead & fence posts south
Post w/sign 1' east
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes Michael Karrick, Deputy Surveyor North between sections 9 and 10 40.00 chs.
Set quarter section post Black Oak 8 in. S33°E 615 links Dug trench.

1-1858 Thomas Hunter (Book A, Page 46, No. 68), County Surveyor, probably uised this corner to set the Center 10.

5-1856 T. Hunter (Book A, Page 5, No. 8 and Old Field Book 13, Page 44-46) used this corner to set the Center 9.

5-1874 T. Hunter (Book A, Page 248, No. 249 and Old Field Book 3, Pages 93-94) found the Center 9 and set the 1/16 West of the Center 9 midway and on line.

9-1876 T. Hunter (Book A, Page 305, No. 300 and Old Field Book 4, Pages 148-149) "found a kind of mound in old fence line and on digging found the remains of old stake in its center. Drove a new stake not marked in its place." He used the corner to set the 1/16 South midway and one line. He also found the Center 9.

9-1886 T. Hunter (Book A, Page 415, No. 404 and Old Field book 14, Page 70) found the stake at the Center 9. Set a new cedar stake properly marked in its place.

2-1892 Thomas Fraser, County Surveyor, (Book A, Page 470, No. 451 and Old Field Book 8, Page 9) could not find the corner. He set a stake midway and one line between the section corners. He used this corner to set the 1/16th East and the Center 10.

5-1900 Robert Fraser, Deputy County Surveyor, (Book A, Page 676, No. 601 and Old Field Book 15, Pages 65 and 66) "found stake which parties said had been set by William C. Fraser, County Surveyor. They thought the stake might have been moved but as it came in line with the fences and hedge row, for purposes of our survey accepted said stake." He used the stake to set the 1/16 North and to set the 1/16 West midway (20.13-1/4) and on line to Hunter's stake he found at the Center 9.

12-1903 Charles Armstrong, County Surveyor, (Book B, Page 70) shows a stake at the W 1/4 Cor. 10, a stake at the 1/64 North, a stake at the 1/16 North, and an iron bar at the 1/16 South (no measurements given).

7-1917 D.R. Williams, County Surveyor, by John Kerr, Deputy County Surveyor, (Book B. P.266 and Kerr Book -10 P.16) shows a stake at this corner and "found stake set in previous survey" 659 North at the 1/64 North.

4-1973 County Surveyor found Hunter's red cedar stake at the Center 9. Projected line from the W 1/4 Cor. 9 over the stake at the Center 9 to the N-S fence at 1/4 Cor. 9-10. Dug the entire area where corner would come to clay but did not find anything.

4-28-1980 County Surveyor set a square pipe with Cast Iron Cap over a 1" square pipe as the corner on the line from the W 1/4 Cor. 9 (found 1971) over the Center 9 (found 1973) and at the location of the N-S fence as found in 1973 survey (fence now gone). Measured 2658.24 West to the Center 9.

11-25-2002 County Surveyor found cast iron cap on telspar pipe down 0.2' in good condition.