Certificate of Location of Government Corner

ID#:531306 **Description:** 1/4 SEC COR 13 14 53 **Date Set:** 4/23/1975 **County:** Olmsted

Section: 13 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in woods
20d nail in E side blazed 15" Basswood N 34.09'
20d spike in N side blazed 23" Oak ENE 12.80' (grown over)
20d spike in NE side blazed 14" Maple in clump of 3 trees SE 20.5' (grown over)
Post w/sign 2' north
This corner is located by GPS reference stations "531306 B & C"

Corner History:

5-1854 Gov't Notes North between sections 13 and 14. 40.00 chs. Set quarter section post. Black Oak 20 in. S50°W 54 lks. White Oak 14 in. N35°E 84 lks.

1-1872 Thomas Hunter (P.190 No.201), County Surveyor, found corner standing.

2-1874 T. Hunter (P.239 No.241) found stake standing.

1-1894 William Fraser (P.541 No.502), County Surveyor, found remains of stake. Set 6"x8"x15" limestone at 1/16 south midway and on line.

McGhie found granite boulder 5"x7"x15" at 1/4 Cor. 13-14 and a limestone at the 1/16 south.

6-26-1970 County Surveyor found boulder with cross at corner. Set stake by stone until CIM can be set. RPs- 10" blazed basswood ENE 12.80, 20D nail 10" maple in clump of 3 trees SE 20.5, 20D nail in 4" elm SSE 17.41, center 2" elm E 4.5.

4-23-1975 County Surveyor set CIM over 1/2" x 15" iron in place of stone found 6-25-1970. Set stone on east side of monument. Also found limestone at 1/16 south.

2-6-2008 County Surveyor found CIM down 0.5' in good condition. Set post w/sign and updated ties.

11-13-2009 County Surveyor found CIM down 0.5' in good condition.