Certificate of Location of Government Corner

ID#:531504 **Description:** 1/4 SEC COR 15 22 53 **Date Set:** 5/17/1972 **County:** Olmsted

Section: 15 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

Bottle cap in W side PP (meas. On the Slope) N 176.0'
Post w/sign 1/2' north
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes M.G. Karrick East Random 15 & 22. 40.00 set temp section post West on true line between section 15 & 22. 40.10 set 1/4 section post 10° 43'. Ashan 6 N 70 E 187. Black Oak 7 S 34 W 170.

6-1886 T. Hunter Bk. A pg. 410 Reset the corner midway and on line.

1-1894 W. Fraser Bk. A pg. 543 Found the corner and set the sixteenth and the sixty-fourth stones to the North.

2-1896 W. Fraser (P591 No.537 S.22) G. Wolf, C. Decker, M. Clark found corner (P410) still no disc of corner. Meas South 39.56 to center sec 22. 2611'

5-17-1972 County Surveyor found a limestone and placed a Cast Iron Monument over the stone and iron rod. RPs-Bottle cap on the W side of the PP (meas. on the Slope) N 176.0'.

1-8-2003 County Surveyor found CIM down 0.4' in good condition. Monument falls inline with fence. Sign & post are 0.6' NNW of CIM.