Certificate of Location of Government Corner

ID#:531604 **Description:** 1/4 SEC COR 16 21 53 **Date Set:** 4/26/1973 **County:** Olmsted

Section: 16 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

Center 2" shaft N 16.6'
20d spike in W side blazed 7" Burr Oak SW 26.4'
20d spike in N side blazed 12" White Oak SE 25.6'
Electric fence post SW 0.4'
Post w/sign 2' south
This corner is located by GPS reference stations "Howl A & B"

Corner History:

1854 Gov't Notes M.G. Karrick, Deputy Surveyor West on true line between sections 16 and 21. 40.00 chs. Set quarter section post. White Oak 10 in. N35°W 178 lks. White Oak 13 in. S45°W 309 lks.

11-1886 Thomas Hunter (P.417 No.406), County Suveyor, found marked stake and tested it with stump of NW bearing tree.

4-1895 William Fraser (P.565 No.518), County Surveyor, found stake.

11-1939 John Kerr (P.544 Book B) County Surveyor, used the corner post on the testimony of a Mr. Amos.

4-20-1972 County Surveyor found old corner post remains used by John Kerr and proved to be as near to corner location as could be found.

4-26-1973 County Surveyor drove 1/2" rod in post remains and set a CIM over. RPs- 16.6 N to center 2" solid iron shaft set in concrete, 25.6 SE to 20D on N side blazed 12" W oak, 26.4 SW to 20D on west side blazed 7" burr oak.

11-26-2002 County Surveyor found CIM at surface in good condition. Set sign & post 2.0' South of monument. Did not check ties.