Certificate of Location of Government Corner

ID#:531806 **Description:** W 1/4 SEC COR 18 53 **Date Set:** 10/18/2007 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CSAH 20, 2' north of fence east and in line with fence west
County Survey Disk in E side PP #50654 NNW 134.43'
Ref pipe E 77.49'
This corner is located by GPS measurement

Corner History:

Gov't Notes 80.00 set post and drove charred stake corneer to sections 7-12-13-18 built mound with trench planted SE osage orange and NE apple seeds.

6-1886 T. Hunter (P411 No.400) found stone set in unrecorded survey 1876 when stake avered by Mr. Sender was found and replaced by stone which lined with fence and fence balko running East and West. Meas North 39.95 to stone found. 1/16 South set stake M & L 19.90.

1943 County Highway Department (book 137 page 56) found limestone (5" x 11" on top split top) in West ditch of road on line with fence running East and West. Disc in T.P. N 77.4'. Disc in F.P. E 36.3.

1947 County Highway Department found stone buried 5' deep, no references.

10-17-1961 J. Kerr found a limestone monument.

6-8-1989 County Surveyor set Ref pipe w/cap East 77.48' on line to 1/2" rod East 174.3'.

10-17-1991 County Surveyor set 1" square pipe w/cap in new blacktop.

1-17-2002 County Surveyor found 1" square pipe w/cap at surface.

4-8-2004 County Surveyor found 1" square pipe w/cap at surface in good condition.

6-4-2007 County Surveyor found 1" square pipe w/eroded cap at surface in good condition. Tied out corner for 2007 overlays.

8-29-2007 County Surveyor removed 1" square pipe w/cap for 2007 overlays.

10-12-2007 County Surveyor set pk nail at surface from 2007 overlay tie out.

10-18-2007 County Surveyor set 1" square pipe w/cap at surface over pk nail.