Certificate of Location of Government Corner

ID#:531904 **Description:** 1/4 SEC COR 19 30 53 **Date Set:** 4/5/2005 **County:** Olmsted

Section: 19 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in E side RR tie CP S 11.56'
County Survey Disk in N side RR tie WSW 12.24'
County Survey Disk in E side 18" Oak NNE 7.43'
County Survey Disk in N side 18" Oak E 10.80'
60d nail used as traverse point SW 9.75'
Post w/sign 2' south
This corner is located by GPS reference stations "Crazy Sue A & B"

Corner History:

1854 Gov't Notes M.G. Karrick. West Random 19 & 30. 40.00 set temp section post. S 89° 50' on true line between section 19 & 30. 40.28 set 1/4 section post. Bur Oak 13 N 6 W 167. Bur Oak 13 S 15 E 63.

6-1886 T. Hunter (Old Field Book #14) 1/4 post missing but found where it stood. Took B.T. (W.O. 6" N 35° W 5 1/2 links).

12-1939 J. Kerr (B.16 P.75 or P.548B S.19) Erwin Chase found boulder as S 1/4 19. Meas East 1627.37 to sec. cor. see 19-20-29-30 which was set midway and likely on line or 2627.5 South from iron at 1/4 19-20.

9-9-1988 County Surveyor found and shot stone 14" x 21" x 14" high with 6" above ground, probably stone used by J. Kerr in 1939, it doesn't seem to have been set more likely filtered in around while setting at surface, 2 trees that could match B.T.'s would throw us 33.5' South will check comp.

10-7-2003 County Surveyor did not find stone.

4-5-2005 County Surveyor found stone lying flat above ground, also found old traverse nail in good condition down 0.4'. Computed final position of 1/4 corner. Set 5' telspar with CIC from computed coordinates up 0.4'. CSD with concrete nail in east side of RR tie used as corner post south 11.56'. CSD with concrete nail in north side of RR ties WSW 12.24', CSD with 60d spike in east side of 18" Oak NNE 7.43', CSD with 60d spike in north side of 18" Oak east 10.80' and 60d nail used as traverse pt. SW 9.75'. Set sign & post 2.0' south.