Certificate of Location of Government Corner

ID#:531905 **Description:** W SEC COR 19 30 53 **Date Set:** 10/18/2007 **County:** Olmsted

Section: 19 **Township:** 105N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CSAH 20, in line with fence west and 22' south of centerline of driveway west
Ref pipe E 110.53'
This corner is located by GPS measurement

Corner History:

Gov't Notes 80.00 set post corner to sections 19-24-25-30. Bur Oak 10 N 5 1/2 W 382. Bur Oak 16 N 70 E 216. Bur Oak 6 S 3 1/2 N 266.

7-7-1965 J.Kerr run line from SW corner 31 to west 1/4 corner 19, an established accepted corner on township line. Set CIM at 3/4 of distance from west 1/4 30 to west 1/4 19. This being equal and straight bu roiginal gov't records. Accepted the corner at west 1/4 31 set by MN Hwy Dept. as it lays or 2638.4 north of twp corner next 2 miles 2631.3 each. RPs- Center of top of steel corner fence post W 48.26, disc in treated fence post in fence line of west road fence running north NW 75.38, corner lies in center north-south road.

6-1-1989 County Surveyor set 1" sq pipe/cap on line from plastic disc in southerly trans. line pole West over C.I.M. top angle at ref pipe to W 19-30 C.I.M. dist. 110.53.

10-17-1991 County Surveyor set 1" sq. pipe w/cap in new blacktop from transit ties.

1-18-2002 County Surveyor found 1" square pipe w/cap at surface.

3-14-2005 County Surveyor found 1" square pipe w/cap up 0.1' in good condition. Pounded pipe down flush with surface.

6-1-2007 County Surveyor found 1" square pipe w/cap at surface in good condition. Tied out corner for 2007 overlays.

8-29-2007 County Surveyor removed 1" square pipe w/cap for 2007 overlays.

10-12-2007 County Surveyor set pk nail at surface from 2007 overlay tie out.

10-18-2007 County Surveyor set 1" square pipe w/cap at surface over pk nail.