Certificate of Location of Government Corner

ID#:532205 **Description:** SEC COR 21 22 27 28 53 **Date Set:** 12/10/2002 **County:** Olmsted

Section: 22 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 7' SW of centerline of residential driveway
NE corner house basement NW 85.15'
Center of 18" Pine SW 71.0'
Punch hole in SW end CMP SE 16.86'
Punch hole in NE end CMP NE 29.85'
County Survey Disk in PP #45951 ENE 40.23'
This corner is located by GPS reference stations "H.D. A & B"

Corner History:

1854 Gov't Notes M.G. Karrick 80.00 set post for cor to section 21,22,27,78. Black Oak 7 S 75 W 228. Bur Oak 8 N 55 W 89. Bur Oak 8 N 55 E 100.

8-17-1964 J. Kerr found 4"-5"-20" Limestone set CIM over stone and brick. RPs-N.E. corner house basement N30°W 85.15 Center of 24" elm. SW 49.0, Center of 18" pipe S.W. 71.0, Disc in TP S 10° E 48.9, Cross in West end 24" galv. Culvert. S 40° E 17.05, Disc in power pole, with transformer, N 50° E 54.6.

11-23-1982 County Surveyor found CIM in good cond. 7' Swly of centerline of private drive running NW-SW Rp's punch hole Swly end of CMP across driveway SE 16.86', Punch hole Nely end of CMP across driveway NE 29.85'.

12-10-2002 County Surveyor found CIM in good condition down 1.1'. Removed CIM and found 1" pipe down 2.8'. Set 5' telspar w/Cast Iron Cap down 0.4' over iron pipe. CSD in PP #45951 40.23' ENE.