Certificate of Location of Government Corner

ID#:532206 **Description:** 1/4 SEC COR 21 22 53 **Date Set:** 5/23/1972 **County:** Olmsted

Section: 22 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1/2' west and 1' north of a steel CP
Post w/sign 2 1/2' SW
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes M.G. Karrick 40.00 set 1/4 section post. Jack Oak 7 N 30 W 32. Aspen 7 N 63 E 75.

6-1886 T. Hunter (Old Fieldbook 14, Page 64) used stake to set the 1/16 East no descrition midway (20.13 1/2) and on line to center 22, a stake.

2-1896 W. Fraser Bk. A pg. 591 Found a cedar stake in mound under the fe. along with the witness tree stumps. Set the sixteenth corner stake North at 1297.56'

4-10-1972 County Surveyor found concrete filled pipe corner post set in massive concrete base.

5-19-1972 County Surveyor found 1/16 stake north side old rotted, but solid 2' long post remains about 2' E of 40D nail set 4-10-1972 as near exact nothing of nail as could be figured. Corner unquestionable correct. RPs- 17.32 Nwly to long conc. Nail in SW side hugh oak, 29.85 NNWly to long conc nail in E side large dead oak. Set 3/4"x4' ele fence post on N & S sides old post & 2"x4" wood as temp witness.

5-22-1972 County Surveyor found near 2" square cedar stake set by W. Fraser 2-1896 on Nwly side concrete mass set around large round steel corner post.

5-23-1972 County Surveyor set CIM over 5/8"x30" reinf. Rod with old stake and small limestone & glass by iron & base of CIM. CIM is .3' west and .8' north center 2 1/2" steel corner post where it enters concrete base.

12-2-2002 County Surveyor found CIM in good condition at surface. Monument falls very close to edge of steep ditch cut. Set sign & post.