Certificate of Location of Government Corner

ID#:532405 **Description:** SEC COR 23 24 25 26 53 **Date Set:** 8/18/1982 **County:** Olmsted

Section: 24 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is up 0.3'
The corner falls NE of CP to fences N-S-E-W
County Survey Disk in W side large Oak 21.15'
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes Michael Karrick, Deputy Surveyor, North between Sections 25 and 26. 80.00 chs. Set post for corner to Sections 23, 24, 25 & 26. Bur Oak 8 in. N60ºE 188 lks. Dug trench.

9-1885 Thomas Hunter, County Surveyor, (Book A, Page 401, No. 391, and Old Field Book 14, Pages 49 an 50) "Section corner missing, but found the corner post at the intersection of old fences running North and South, and also running West forming the dividing lines between different farms, and Mr. Thos. Stuckman, an old resident avers that he built the fence running West, and that he set the corner post as found, in the center of the mound where the original corner stood. We therefore dug up the remains of the old post and set stone in its place 14x6x6 inches as the corner." He used this corner to set 1/4 Cor. 25-26, and 18x6x2 inch stone midway (39.99 chs.) and on line to the SW Cor. 25 (stone and stake found). He set a stake at the 1/16 South of 1/4 Cor. 25-26 midway (19.99-1/2 chs.) and on line to 1/4 Cor. 25-26 as set, and set a quarry stone at the 1/16 South of 1/4 Cor. 25-26 midway (19.99-1/2 chs.) and on line to the SW Cor. 25. He measured East 1-1/2 miles to 1/4 Cor. 19-30, T105N, R12W, to set the NE Cor. 25 E-W at 80.00 chs. East. Measured 40.07 chs. East to set a 1/4 Cor. 24-25 from bearing trees.

9-1885 Hunter (Book A, Page 403, No. 392, and Old Fieldbook 14, Pages 51 and 52) found corner set Page 401. He set a 14x3x3 inch stone, midway (20.03-1/2 chs.) and on line to 1/4 Cor. 24-25 at the 1/16 East. He set a temporary stake at the 1/16 North midway (19.89-1/2 chs.) and on line to 1/4 Cor. 23-24.

4-1895 William Fraser, County Surveyor, (Book A, Page 563, No. 517) "found corner as set by Hunter in Survey 392, Page 403." He used the corner to set 1/4 Cor. 23-26, a stone 22x3x3 inches with a stake by its side, midway (39.83 chs.) and on line to the SW Cor. 23, a stone set this survey. He also set the 1/16 West of 1/4 Cor. 23-26, a stone and stake. He shows a measure North of 39.79 chs. to 1/4 Cor. 23-24.

7-19-1972 County Surveyor found a 6" square limestone 1-1/2' N.E.'ly of the corner post of fences. Also found Fraser's stones at 1/4 Cor. 23-26 and at Sec. Cor. 22-23-26-27. Could not find Fraser's stone at the 1/16 West of 1/4 Cor. 23-26. Set a 3/8" electric fence post on the South side of stone found.

7-23-1982 County Surveyor found a 2-1/2"x3-1/2"x13" pointed limestone at the 1/16 East. Stone .83 North and 1.26 West of the midway (1322.01) and on line point to 1/4 Cor. 24-25 as set this survey.

8-18-1982 County Surveyor drove a drill steel on the North side of the stone found 1972 and left the 3/8" electric fence post on the South side of stone (bent over). Set a Cast Iron Monument directly on top of the stone. Measured North 2626.12 to 1/4 Cor. 23-24 set this survey. Measured 2636.81 South to 1/4 Cor. 25-26 (CIM over stone found 1973). Measured 2628.74 West to 1/4 Cor. 23-26, then 2627.12 to Sec. Cor. 22-23-26-27 and found 1/4 corner on line to Sec. Cor. 22-23-26-27.

11-3-2010 County survey crew found CIM in good condition.