Certificate of Location of Government Corner

ID#:532904 **Description:** 1/4 SEC COR 29 32 53 **Date Set:** 5/22/1987 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of fence north and in centerline of E-W twp road
County Survey Disk in E side CP NNE 27.51'
County Survey Disk in W side CP S 26.35'
County Survey Disk in NW side 16" Pine (near bottom) NE 77.05'
This corner is located by GPS reference stations "DJC & Collins"

Corner History:

1854 Gov't Notes M.G. Karrick East Random 40.00 set temp 1/4 section post 29 & 32. West on true line between section 29 & 32. 40.00 set 1/4 section post 7° 45'. Bur Oak 7 S 10 E 76. Bur Oak 13 N 5° E 82.

8-1964 J.Kerr; Run & meas north line 32 and found NE corner 32. Meas total mile 5266.33. In passing 1/4 29-32 set 120D 2' north of center road at 2635.0 in line fence north which is 23.4 south of corner post of new fence running north and lines roughly with old fence running south. Missed section corner east 7.92' north. To place this corner M & L 2633.16 this 120D must go 3.96' south and 1.84' west.

5-20-1987 County Surveyor found spike set by Kerr in 1964 on random line and in line fence South. Dug from 1' S of spike South for 7' + E 4' W 5' Old road on clay 3 1/2' deep very poor condition M & L by DRWG 4-19 comes 393 South and 1.95 W of spike. Found only a spike approx. 4' S of Kerr spike and in centerline road.

5-22-1987 County Surveyor, after remeasuring sec line set CIM over 1/2" re-rod on line between the section corners and in line with fence South. Corner now 2' W of newer board fence running North corner in centerline E-W road. CSD in E side CP NNE 27.51'. CSD in W side CP S 26.35. CSD in NW side (near bottom) NE 77.05' 16" pine.

7-20-2000 County Surveyor found CIM down 0.7' in good condition.