Certificate of Location of Government Corner

ID#:533205 **Description:** S SEC COR 31 32 53 **Date Set:** 6/25/1981 **County:** Olmsted

Section: 32 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under E-W fence and 10' east of fence south
County Survey Disk in 14" Pine NNW 28.89'
County Survey Disk in 16" Pine W 21.37'
Post w/sign 1' north
This corner is located by GPS refrence stations "430508 and Hale"

Corner History:

1853 Gov't Notes E. Norris, Deputy Surveyor, 80.00 chs. Set post for corner to Sections 31 and 32. Built mound with trench per instructions. Drove charred stake in center and planted apple tree seed in NW corner.

9-1893 William C. Fraser, Deputy County Surveyor, (Book A, Page 528, No. 493) could not find this corner. He set a 24"x12"x4" stone "on line and according to measurement (prorated Gov't measure) between A (SW Cor. 31) and F (S 1/4 Cor. 33)." He used this corner to set 1/4 Cor. 31-32, a 27"x9"x3" stone, midway (39.94 chs.) and on line to Section Cor. 29-30-31-32. He also set the 1/16 North, a 18"x15"x3" stone, midway (19.97 chs.) and on line.

4-1942 John Kerr, County Surveyor, (Kerr Book 27, Page 4) possibly found corner. He found the stones at the 1/16 North, 1/4 Cor. 31-32, and Sec. Cor. 29-30-31-32. States (at S 1/4 Cor. 32) "limestone in place 2639.8 East of SW Cor."

4-24-1981 Roger Brand, Olmsted County Surveyor, and Dave Knutson, Fillmore County Surveyor, found a limestone with a 2"x6" top--bottom of stone much larger, but did not dig up except top part (± 14"). Corner is under E-W fence line and is ± 10' East of fence corner to fences South and East.

5-5-1981 Olmsted County Surveyor dug for Fillmore County Surveyor in line with fence west and on west 1/2 of N-S road. Didn't find W.Fraser's 22x10x2 stone. We did find a pointed boulder 10x14x17 dug well down into clay with smaller boulder packed around about 3' deep. Fillmore County Surveyor tied this stone into his section 5 traverse. 1/16 North of center 5- dug on west shoulder of N-S road and found 13x14 rectangle mark in clay with small piece of limestone about 3' seep. Found nothing further. The Fillmore County Surveyor tied this point into his section 5 traverse. 1/4 corner 5-8; dug centered approx. 1' west of fence south and in the center of the E-W road. Dug 4' + to clay, but found nothing. N 1/4 corner 5; Fillmore County Surveyor set CIM midway between NW 5 and NE 5 and on line SW 31 to SE 31. RPs- corner 27;' west of centerline of rock road and 3.5' south of fence running west, nail with blue plastic in NW face of PP WSW 9.69, nail with blue plastic in SW face of 3rd pine north of fence NW 39.48.

6-25-1981 Olmsted County Surveyor removed stone and set a Cast Iron Monument over a 1/2" iron as the corner. Put the stone on the South side of the CIM RPs-CSD & spike in 14" pine NNW 28.89, Spike and CSD in 16" pine West 21.37, 10' ± east of fence south.

8-20-1982 1/16 North: Olmsted County Surveyor dug with backhoe from t.n. set in 19--. First found a 3" x 11" x 17" shattered limestone (3 pieces) dug in and standing top down 20" (this stone 1.3 S of Will Fraser's stone found next). Dug further and found Will's recorded stone standing just North of the shattered stone and 2.45 East and .1 North of the road surface and .3 E and .2 N of the center of Will's stone.(t.n. E 8.80, S 7.80) (hub-E 6.15, SSW 8.20) (1st stone-ENE 6.70 SSW 6.66).

9-19-2006 Olmsted County Surveyor found CIM down 0.1' in good condition.