Certificate of Location of Government Corner

ID#: 533209 **Description:** SEC CEN 32 53 **Date Set:** **County:** Olmsted

Section: 32 **Township:** 105N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-1-1942 John Kerr, County Surveyor, (John Kerr Field Book #27, Page 4) set 1/2"x2-1/2"x30" iron bar midway and on line at 2637.62' on east-west quarter line. RPs - Spike in power pole NE 39.0', Center 18" Elm SW 34.33'.

1953 Minnesota Highway Department Trunk Highway 30 rollmap shows 1/2"x1-1/2" iron bar 11.8' north of centerline at P.O.T. Sta 211+18.8.

12-8-1980 Roger Brand, County Surveyor, dug and found nothing.

11-14-1986 Tom Ferguson set RR spike at intersecting quarter lines.

3-28-1987 Tom Ferguson found and used RR spike.

4-19-2007 County Survey Crew searched and found nothing.

9-21-2009 Jerome Schwarz used computed center at intersecting quarter lines.

10-31-2012 Jerome Schwarz used computed center at intersecting quarter lines.