Certificate of Location of Government Corner

ID#:533305 **Description:** S SEC COR 32 33 53 **Date Set:** 6/9/1978 **County:** Olmsted

Section: 33 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls on SW side of CP to fences E-W-N (burned)
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes E. Norris, Deputy Surveyor West on the south boundary of section 33. 80.00 chs. Set post for corner to sections 32 and 33. Made mound with trench and drove charred stake in center and planted apple seed in NW corner.

5-1893 William Fraser, County Surveyor (Book A P.528 No.493) could not find this corner. Set a 3"x10"x24" stone on line from the S 1/4 corner 33 to the SW corner 31 and at prorated Gov't measure (i.e. 1/5 the total distance).

7-1930 Olmsted County Highway Department (C.H.D. Book 57 P.44) found the recorded stone.

4-1942 John Kerr, County Surveyor, (Kerr Book 27 P.4) found the stone.

5-31-1978 Olmsted County Surveyor found a 3"x10" topped limestone down 1' on the SW side of the corner post.

6-9-1978 Olmsted County Surveyor broke off the top 6" of the stone and set a CIM over the stone with a 1/2"x40" iron along side of the stone. The corner falls on the SW side of the corner post to fences E-W-N. RPs- fence line south , west 140' ±, nailed survey marker sign on corner post.

8-17-2009 Olmsted County Surveyor found CIM up 0.3' in good condition.