Certificate of Location of Government Corner

ID#: 533504 **Description:** S 1/4 SEC COR 35 53 **Date Set:** 6/4/1981 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.7'
The corner falls 2.5' north of centerline E-W twp. road and in line with fence north.
County Survey Disk in CP N 45.46'
This corner is located by GPS measurement.

Corner History:

1853 Gov't Notes E. Norris, Deputy Surveyor, West on the South boundary of Section 35. 40.00 chs. Set quarter section post. Built mound with trench per instructions. Drove charred stake in center and planted apple tree see in N.W. corner.

11-1853 Gov't Notes Phipps and Fitzpatrick, Deputy Surveyors, North between sections 1 and 2. 78.20 chs. Intersect N. boundary 250 lks. West of corner and set a stone 15 inches long 10 broad and 4 thick for corner to Sections 1 and 2.

9-1893 William Fraser, Deputy Co. Surveyor, (Book A, P. 528, No. 493) dug for this corner but could not find it.

6-4-1981 Olmsted County Surveyor dug for this corner. Found stake hole after scraping an 18" diameter dark spot down about 1/2'. The stake hole went down approx. 1' into clay. Set a 5/8"x18" iron in the stake hole with junk round it. Set a Cast Iron Monument over a 5/8"x16" rod at the road surface. The corner is 166.09' E'ly of a 1" square pipe set over the stone found at North 1-2, T104N, R13W, on 6-2-1981.

10-28-2010 Olmsted County survey crew found CIM in good condition.