Certificate of Location of Government Corner

ID#: 533506 **Description:** 1/4 SEC COR 34 35 53 **Date Set:** 8/18/1982 **County:** Olmsted

Section: 35 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.9'
The corner falls in line with fence south and 3.5' south of centerline E-W township road.
Punch mark in top 2" shaft CP SSW 26.68'
This corner is located by GPS measurement.

Corner History:

5-1854 Gov't Notes Michael Karrick, Deputy Surveyor, North between sections 34 and 35. 40.00 chs. Set quarter section post in mound with trench, pits, and charred stake.

8-2-1982 County Surveyor dug with backhoe in the center of the E-W road and in line with the fence South. Found a 2"x28" stake, top down 4-1/2', extending 2' into clay. The top 2/3's of the stake had been dug around. Removed the stake to the office and drove a square (telspar) pipe in its place. Set a 1" square pipe at the road surface.

8-5-1982 County Surveyor dug at the Center 34 but did not find anything.

8-18-1982 County Surveyor drove the 1" square pipe set 8-2-1982 down and set a Cast Iron Monument over it. We could not find any records of surveys on this corner; however, we did find two deeds from 1866 which we can combine to give a total measure of 2631.42 North to Sec. Cor. 26-27-35-36. We now measure North 2633+ to the projection of the fence from the West at Sec. Cor. 26-27-35-36. We find the fence South at the 1/16 West of 1/4 Cor. 34-35 as found to be midway to the fence North at the Center 34 and the fence corner at the Center 35 is 2-1/2' North of the E-W 1/4 line.

10-28-2010 County survey crew found CIM in good condition