Certificate of Location of Government Corner

ID#: 533604 **Description:** S 1/4 SEC COR 36 53 **Date Set:** 9/9/1982 **County:** Olmsted

Section: 36 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.1'
The corner falls 7' north of centerline of E-W twp road & 4' west of centerline field entrance north.
County Survey Disk in PP #13375 NNE 36.37'
Punch mark in N end 60" CMP ENE 50.36'
This corner is located by GPS measurement.

Corner History:

1853 Gov't Notes Elisha S. Norris, Deputy Surveyor, West on South boundary of Section 36. 40.00 chs. Set quarter section post and built mound with trench per instruction. Drove charred stake in center and planted Apple seed in NW corner. 42.20 chs. Brook 3 lks. wide runs SE.

1853 Gov't Notes Elisha S. Norris, Deputy Surveyor, North between Sections 1 and 6 (between Ranges 12 and 13, T104N) 79.30 chs. Brook 2 lks. wide runs SE 79.67 chs. Intersect 1st Standard Parallel 286 links West of Quarter Sec. Cor. to Section 36, T105N, R13W, and set post corner to Township 104 of Ranges 12 & 13 West-- 5th Mer. Built mound with trench, NE planted Apple seeds. At center drove charred stake.

6-3-1981 Olmsted County Surveyor found the township monument at the NE Cor. 1, T104N. Set a 1" square pipe at surface. Corner is in centerline of road south & 6' north of centerline E-W road. RPs- chisel cross in N end 60" culv ENE 38.91, chisel cross S end 60" culv SE 57.01, chisel cross W end 60" culv SW 69.54.

6-4-1981 Olmsted County Surveyor dug for the corner on the Gov't tie from the NE Cor. 1, T104N, R13W. Could not find the corner. Conditions very poor.

9-9-1982 Olmsted County Surveyor set a Cast Iron Monument over a 3/4"x15" iron as the corner. The corner is set on the line from the S Sec. Cor. 35-36 over the NE Cor. 1, T104N, R13W, and at the Gov't tie (188.76) East of the NE Cor. 1, thus accepting and preserving the NE Cor. 1 found as having been properly set, although we do not have a record of the survey. RPs- CSD in PP #13375 NNE 36.37, punch mark in N end 60" CMP ENE 50.36.

10-28-2010 County survey crew found CIM in good condition.