# Certificate of Location of Government Corner

**ID#:** 533606 **Description:** 1/4 SEC COR 35 36 53 **Date Set:** 9/10/1982 **County:** Olmsted

**Section:** 36 **Township:** 105N **Range:** 13W **Monument Description:** Cast Iron Monument

**Reference Ties:**

The monument is down 0.9'
The corner falls in line with fences east and west and 2 1/2' west of centerline of N-S twp road
Punch hole in N end CMP NW 36.05'
County Survey Disk in S side CP E 36.99'
Nail in SW face gate post SE 43.60'
This corner is located by GPS measurement.

**Corner History:**

5-1854 Gov't Notes Michael Karrick, Deputy Surveyor, North between sections 35 and 36. 28.71 chs. Wagon Road bears NW. 40.00 chs. Set quarter section post in mound with pits, trench, and charred stake and Osage Orange seeds NE and SW We could find no other records of surveys at this corner.

6-5-1981 County Surveyor dug for this corner from a point in the center of the N-S road and in line with the fences East and West for 3' East, 6' North, 6' West and 5' South.

9-10-1982 County Surveyor set a Cast Iron Monument over a 3/4" re-rod as the corner on line between the section corners and in line with the fences East and West. RPs- CSD in S side corner post to fence E, E 36.99, punch hole top north end CMP in field drive NW 36.05. We accepted the fence line for N-S control instead of the midway position (which is 4.08 North) since it holds the fence at the 1/16 North midway to Sec. Cor. 25-26-35-36 and holds the fence at the 1/64 North of S Sec. Cor. 35-36 close to 1/4 the distance from S Sec. Cor. 35-36 to 1/4 Cor. 35-36.

7-2004 Yaggy Colby Survey Crew found monument in good condition just below road surface.

10-28-2010 County survey crew found CIM in good condition.