Certificate of Location of Government Corner

ID#: 540304 **Description:** 1/4 SEC COR 3 10 54 **Date Set:** 4/23/1976 **County:** Olmsted

Section: 03 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 14 1/2' east of N-S fence on side hill
County Survey Disk in SE side blazed 22" Oak SW 22.6'
Steel fence post 2' west
Post w/sign 1 1/2' north
This corner is located by GPS reference stations "Nigon A & B"

Corner History:

1853 Gov't Notes William Yerby, Deputy Surveyor West on true line between sections 3 and 10. 39.85 chs. Set a quarter section post. Black Oak 8 in. N30°W 42 lks. Burr Oak 13 in. S15°E 88 lks.

6-1876 Thomas Hunter (P. 299 No. 294), County Surveyor, found stake. Set marked stake at the 1/16th East midway and on line.

4-23-1976 County Surveyor dug 4' x 4' x 3' deep to clay but found nothing. Set CIM over 5/8" x 18" rod as corner at double the line and measure from Sec. Cor. 2-3-10-11 over the 1/16th West (found).

7-3-1990 County Surveyor found CIM in good shape but post set north of it in 1976 had been moved ±25 Nwly west of fence, also a lath by it. Set sign & post 1.0' north, also other steel fence post 2' west of CIM, we also set a trav. Iron 225.08 Sely in field.

4-1-2004 County Surveyor found CIM down 0.2' in good condition.