Certificate of Location of Government Corner

ID#: 540406 **Description:** 1/4 SEC COR 4 5 54 **Date Set:** 12/22/1986 **County:** Olmsted

Section: 04 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' SW of CP
County Survey Disk in S side brace post W 10.04'
County Survey Disk in W side brace post N 12.26'
Sign on CP 1' NE
This corner is located by GPS measurement

Corner History:

No old records

1964 J. Kerr Bk 89 P.33-34 says "stone" as 1/4 corner with ties. Kerr apparently set the Center Sec. 5 from this 1/4 Cor. although notes are confusing.

1-26-1959 McGhie & Betts Survey in SW 1/4 Sec. 4 Set 1/2" rod in fence intersection. - Meas. So. 2607.7'. Set 1/16 Cor. South 5/8" rod - 18 ft. N of fence East. See copies of field notes in Blue book - Sec. 4

1-1961 County Surveyor found stone and left as found. RPs- State Reference point in TP SW 42.3', State Reference point in tele pole NE 41.2', State Reference point in pp NW 46.6'.

12-15-1986 County Surveyor dug from the CP to fences N-S-E-W for 2'+W 2'N .2' E & 3' So FD McGhie's 1/2" rod 1.2 SW of CP & 1.5±E, Dug under N-S fence from approx. 10' to 20' N of CP 2'E & 2'W of fence.

12-22-1986 County Surveyor accepted fence corner as corner & drove long telspar/CIC at location of McGhie rod (removed) corner 1' SW of present CP with sign. CSD side of brace post W 10.04, CSD in W side of brace post N 12.26.

7-20-2004 County Surveyor found cast iron cap on telspar pipe up 0.3' in good condition.