Certificate of Location of Government Corner

ID#: 540605 **Description:** W SEC COR 6 7 54 **Date Set:** 11/13/1972 **County:** Olmsted

Section: 06 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of centerline of N-S twp road and 3' south of centerline of twp road west
Single punch mark in S end 30" CMP ENE 30.1'
North end. culv. (16' long culv.) NE 36.22'
Single punch in S end 48" CMP WSW 42.52'
Single punch in N end 48" CMP WNW 43.23'
This corner is located by GPS measurement

Corner History:

4-1872 T. Hunter P. 194 No. 205 found long stone set as corner. Meas. east to stake found standing & marked stumps of said 1/4 6-7 witness trees. -16 E set corner at prop. meas. at 19.34 (1276.44) then 19.87 (1311.42 to N 1/4 stake 16" br. oak S 8°E 70 lks 46.20' 12" br. oak N 8-1/2°W 79 lks. 52.14' - 16 S. set marked stake M & L 19.90 (1313.4) 8" br oak N 46-1/2 E 107 lks. (70.62 = 3" br oak S53°E 51 lks. 33.66 16 center NW 1/4 7. set stake at inters 1/16 line 1 mile each. Meas. W 19.35 (1277.1 E 1304.82 (19.77)

4-1876 T. Hunter P. 291 No. 286 "found stake in mound undisputed" a quote contradicting information of survey P. 194. Note old field book survey No. 286 says found stone as described - meas. mile west 80.13 set temp. joint M & L 40.06-1/2 (2644.3).

9-1913 D. Williams "Could find no corner at "B" West 7-18 but found upright limestone with rotted stake beside it at "A" west 6-7 105-14. Located in west wheel track in line with fence running east. Ole Rud and Mr. Rasmussen said this was the correct coner. Ran & meas. line to boulder 2 miles south each 1/2 mile 2634.0 SW7 set 1/2"x2' rod. W 1/4 7 set post M & L came in east ditch 10' N of fence west.

11-13-1972 County Surveyor found 3/4" iron set by recent surveyor in line fence east and center N-S road. - Dug with backhoe, found vertical limestone 4"x8" cap about 14 to 16" long 4.6' down 2.28 W .62 S of iron in near exact line fence east. 2' west center N-S roads 2' south road west - set farm tile filled with concrete with 1/2" reinfor. rod in center over stone with CIM over corners

11-1-1982 County Surveyor, at 1/16 East: Dug appx. 4' diameter centered 20' west of t.n. Clean clay down 1'. Found good mark of stake 1.2 SE'ly of the center of a 1' diameter post mark. Mark extending 1' into clay and tapered to a point. Left spike in mark. will shoot later. Meas. 19.03 from t.n. to stake. RP's: Conc. nail in So side corner post W 5.25 Spike in Oak NW 8.71.

3-15-2006 County Surveyor found CIM down 1.1' in good condition.