Certificate of Location of Government Corner

ID#: 540806 **Description:** 1/4 SEC COR 7 8 54 **Date Set:** 8/10/1970 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

County highway disk in SE side CP NE 2.6'
Bottle cap in NE side PP #9972 SE 66.6'
County highway disk in W side CP S 64.43'
Sign on CP 2 1/2' NE
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Yerby 40.00 set 1/4 sect. post Burr Oak 12 in N 65 W 49 lks. Burr Oak 6 in. S 74 E 394 lks.

4-1872 T. Hunter P. 194 No. 205. Witness trees grubbed and gone, found stake in fence averred by Mr. Oleson as site of orig stake which he carefully preserved bearing north half N 0°27'E S 1/2 N 1° 25' E - 16 S set stake M & L 19.89 (13.12.74 & took B trees. 8" br. oak S 32°E 32-1/2 lks. (21.45 - 12" br. oak N 32° W 178 lks. 117.5 -16 N set stake M & L 19.63 (1295.58' x 2 = 2591.16'.

8-1887 Thos. Fraser P. 434 No. 421 found fence post averred by same Mr. Oleson as placed there in place of orig stake, being with Hunter P. 194 - 16 S found hunters S E B T. Set new stake and set new B.T. 6" Bl. Oak N 48E 3/4 22L 9.57N & 10.92 E 14.5'.

8-10-1970 County Surveyor found stone and set CIM over 3/4" x 18" reinf. rod and glass with small flat stones - stone found on N side - a thin 6" x 18" stone on west side of CIM 8" away±.

1981 See T. Taylor survey in Sec. 8 - Vertical File, Survey Data, Range 14.

10-7-1982 County Surveyor found CIM in good condition. All 1970 RP's in place. Nailed survey marker sign to CP NE of corner 2-1/2'.

7-28-2000 County Surveyor found CIM in good condition.